

Linksys PAP2 Configuration - Windows Internet Explorer

http://[IP]/admin/advanced

File Edit View Favorites Tools Help Transaction Protector LPBCONSULT

Home Feeds (1) Print

Discontinue Call Waiting Tone Patterns

CWT1 Cadence: 30(3/9.7) CWT2 Cadence: 30(1/1, 1/9.7)
 CWT3 Cadence: 30(1/1, 1/1, 1/9 CWT4 Cadence: 30(1/1, 3/1, 1/9.
 CWT5 Cadence: 1(5/5) CWT6 Cadence: 30(1/1, 3/2, 3/9.
 CWT7 Cadence: 30(3/1, 3/1, 1/9. CWT8 Cadence: 2.3(3/2)

Distinctive Ring/CWT Pattern Names

Ring1 Name: Bellcore-r1 Ring2 Name: Bellcore-r2
 Ring3 Name: Bellcore-r3 Ring4 Name: Bellcore-r4
 Ring5 Name: Bellcore-r5 Ring6 Name: Bellcore-r6
 Ring7 Name: Bellcore-r7 Ring8 Name: Bellcore-r8

Ring and Call Waiting Tone Spec

Ring Waveform: Sinusoid Ring Frequency: 25
 Ring Voltage: 85 CWT Frequency: 425@-10
 Synchronized Ring: no

Control Timer Values (sec)

Hook Flash Timer Min: .1 Hook Flash Timer Max: .9
 Callee On Hook Delay: 0 Reorder Delay: 5
 Call Back Expires: 1800 Call Back Retry Intvl: 30
 Call Back Delay: .5 VMWI Refresh Intvl: 0
 Interdigit Long Timer: 10 Interdigit Short Timer: 3
 CPC Delay: 2 CPC Duration: 0

Vertical Service Activation Codes

Call Return Code: *69 Blind Transfer Code: *98
 Call Back Act Code: *66 Call Back Deact Code: *86
 Cfwd All Act Code: *72 Cfwd All Deact Code: *73
 Cfwd Busy Act Code: *90 Cfwd Busy Deact Code: *91
 Cfwd No Ans Act Code: *92 Cfwd No Ans Deact Code: *93
 Cfwd Last Act Code: *63 Cfwd Last Deact Code: *83
 Block Last Act Code: *60 Block Last Deact Code: *80
 Accept Last Act Code: *64 Accept Last Deact Code: *84
 CW Act Code: *56 CW Deact Code: *57

Done Internet 100% 10:23

Særlige indstillinger for PAP2T, når der anvendes en Beocom 6000 analog telefon.
 Åben fanen: "Admin login" og skift til "Advanced View", "Regional Settings".
 Prøv evt. at justere "Ring Voltage" til 90V og/eller "Ring Frequency" til 32 eller 64

Linksys PAP2 Configuration - Windows Internet Explorer

http://[IP]/admin/advanced

Transaction Protector LPBCONSULT

Home Feeds (1) Print

Vertical Service Announcement Codes

CODE: []

Attn-Xfer Act Code: [] Modem Line Toggle Code: *99

Media Loopback Code: *03

Referral Services Codes: []

Feature Dial Services Codes: []

Service Annc Base Number: []

Service Annc Extension Codes: []

Outbound Call Codec Selection Codes

Prefer G711u Code: *017110 Force G711u Code: *027110

Prefer G711a Code: *017111 Force G711a Code: *027111

Prefer G723 Code: *01723 Force G723 Code: *02723

Prefer G726r16 Code: *0172616 Force G726r16 Code: *0272616

Prefer G726r24 Code: *0172624 Force G726r24 Code: *0272624

Prefer G726r32 Code: *0172632 Force G726r32 Code: *0272632

Prefer G726r40 Code: *0172640 Force G726r40 Code: *0272640

Prefer G729a Code: *01729 Force G729a Code: *02729

Miscellaneous

Set Local Date (mm/dd): [] Set Local Time (HH/mm): []

Time Zone: GMT+01:00 FXS Port Impedance: 600

Daylight Saving Time Rule: start=4/-1/7;end=10/1/7;save=1

FXS Port Input Gain: -3 FXS Port Output Gain: 600+2.16uF

DTMF Playback Level: -16 DTMF Playback Length: 270+750||150nF

Detect ABCD: yes Playback ABCD: 220+820||120nF

Caller ID Method: DTMF(Denmark) FXS Port Power Limit: 220+820||115nF

Caller ID FSK Standard: bell 202 Feature Invocation Method: Default

More Echo Suppression: no

Save Settings Cancel Settings

CISCO SYSTEMS

Bemærk øvrige indstillinger for PAP2T, når der anvendes en Beocom 6000 analog telefon: "FXS Port impedance" kan indstilles til 270+750||nF (default 600). Øvrige DTMF indstillinger m.v. som vist på denne side.